

### Bid Document

Bid Details	
Bid End Date/Time	22-01-2021 21:00:00
Bid Opening Date/Time	22-01-2021 21:30:00
Bid Life Cycle (From Publish Date)	90 (Days)
Bid Offer Validity (From End Date)	75 (Days)
Ministry/State Name	Ministry Of Health And Family Welfare
Department Name	Department Of Health And Family Welfare
Organisation Name	HII Infra Tech Services Limited
Office Name	Hites
Total Quantity	1355
Item Category	Revolving Chair , Chairs-Office- IS 3499 , Sofas , Centre Table , Executive Table
Bidder Turnover (Last 3 Years)	35 Lakh (s)
OEM Average Turnover (Last 3 Years)	280 Lakh (s)
Experience Criteria	3 Year (s)
MSE Exemption for Years of Experience and Turnover	No
Startup Exemption for Years of Experience and Turnover	No
Document required from seller	Experience Criteria,Past Performance,Bidder Turnover,Certificate (Requested in ATC),OEM Authorization Certificate,OEM Annual Turnover,Additional Doc 1 (Requested in ATC),Additional Doc 2 (Requested in ATC),Additional Doc 3 (Requested in ATC),Additional Doc 4 (Requested in ATC) *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer
Past Performance	50 %
Bid to RA enabled	No
Primary product category	Executive Table
Time allowed for Technical Clarifications during technical evaluation	3 Days
Inspection Required	Yes
Inspection to be carried out by Buyers own empanelled agency	Yes
Type Of Inspection	Post Dispatch
Name of the Empanelled Inspection Agency/ Authority	Board of Officers
Evaluation Method	Total value wise evaluation

### EMD Detail

Advisory Bank	State Bank of India
EMD Percentage(%)	2.00
EMD Amount	139988

**ePBG Detail**

Advisory Bank	State Bank of India
ePBG Percentage(%)	5.00
Duration of ePBG required (Months).	40

(a). EMD EXEMPTION: The bidder seeking EMD exemption, must submit the valid supporting document for the relevant category as per GeM GTC with the bid. Under MSE category, only manufacturers for goods and Service Providers for Services are eligible for exemption from EMD. Traders are excluded from the purview of this Policy.

(b). EMD & Performance security should be in favour of Beneficiary, wherever it is applicable.

**Beneficiary:**

AVP (IDD) & Head (IDS)

HLL Infratech Services Limited, A Government of India Enterprise under Ministry of Health and Family Welfare, Golden Jubilee Block, HLL Bhawan, Poojappura P.O., Thiruvananthapuram, Kerala  
(Ranjith Kumar. A)

**Splitting**

Bid splitting not applied.

1. Experience Criteria: In respect of the filter applied for experience criteria, the Bidder or its OEM {themselves or through reseller(s)} should have regularly, manufactured and supplied same or similar Category Products to any Central / State Govt Organization / PSU / Public Listed Company for number of Financial years as indicated above in the bid document before the bid opening date. Copies of relevant contracts to be submitted along with bid in support of having supplied some quantity during each of the Financial year. In case of bunch bids, the category of primary product having highest value should meet this criterion.
2. OEM Turn Over Criteria: The minimum average annual financial turnover of the OEM of the offered product during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the OEM is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria.
3. Past Performance: The Bidder or its OEM {themselves or through re-seller(s)} should have supplied same or similar Category Products for 50% of bid quantity, in at least one of the last three Financial years before the bid opening date to any Central / State Govt Organization / PSU / Public Listed Company. Copies of relevant contracts (proving supply of cumulative order quantity in any one financial year) to be submitted along with bid in support of quantity supplied in the relevant Financial year. In case of bunch bids, the category related to primary product having highest bid value should meet this criterion.

**Revolving Chair ( 25 pieces )**

**Technical Specifications**

[\\* As per GeM Category Specification](#)

Specification	Specification Name	Bid Requirement (Allowed Values)
MATERIAL	<b>Pedestal Base</b>	Chrome finish with 5 wheels
	<b>Arm Material</b>	pu foam bonded chrome coted
	<b>seat material</b>	PU Foam Covered With pure leatherite
	Density of PU foam used in seat KG per Cu Meter (+/- 3)	35
	Density of PU foam used in backrest in KG per Cu Meter (+/- 3)	35
	<b>Material of Fabric Back Cover / Material for Backrest</b>	Leatherite, N.A
	<b>Material of Fabric of Seat Cover</b>	leatherite
	GSM/Thickness of fabric ±5%(Gram/Square meter)	N.A
GENERAL	<b>Chair Type</b>	central tilt synchronic
	Tilt Tension Adjustment	Yes
	<b>Height Adjustment ± 5(mm)</b>	up to 120 mm
	<b>Arm</b>	With
	<b>Type of backrest support</b>	backrest symmetrical lumber support
	<b>Arm Type</b>	Fixed
	Colour of Fabric for Seat and Backrest	brown
	<b>Ergonomic Seat Design</b>	Yes
	<b>Back type</b>	push back
	Backrest is made of two pcs injection moulded frame	Backrest is made of two pcs injection moulded frame
	<b>backrest has separate adjustable headrest</b>	Yes, No
	<b>Seat type</b>	fixed
	Seat is curved	Yes
	Locking mechanism	Yes
	Type of locking	upright locking
<b>Number of arm movement</b>	N.A	
<b>Lumber support</b>	integrated	
DIMENSION	<b>Overall Chair Height ±15mm</b>	1180
	<b>Backrest Height ±15mm</b>	570.0
	<b>Backrest Width ±10mm</b>	550.0
	<b>Seat Height ±15 mm</b>	500
	<b>Seat Width ±10 mm</b>	500
	<b>Seat Depth ±10 mm</b>	500.0
	<b>Thickness of MS Plate Joining the under structure with Seat</b>	0.8
	<b>Thickness of Plywood used in Seat ±1(mm)</b>	15 mm
	<b>Thickness of Plywood used in Backrest ± 1(mm)</b>	15 mm

	Padestal Size (Diameter in mm) +/- 10 mm	680
	<b>Thickness of Polyurethane Foam Used in Seat in mm (+/- 2 mm)</b>	25 mm
	<b>Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 2 MM)</b>	25 mm
WARANTEE	<b>Warrantee period in number of years</b>	1-year
CERTIFICATION	<b>Test reports to be furnished to buyer on demand</b>	NO
	<b>BIFMA Certification</b>	NO
	<b>OEM of offered product is ISO 9001:2015 certified</b>	YES
	<b>OEM of offered product is ISO 14001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 18001:2007 certified</b>	NO
	<b>Green guard certification</b>	NO
	<b>Aiota</b>	NO

#### Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Delivery Schedule (In number of days from contract start days)		
1	K B R Deepti	508126,Bibinagar	Quantity	Delivery to start after	Delivery to be completed by
			25	25	35

#### Chairs-Office- IS 3499 ( 30 pieces )

##### Technical Specifications

[\\* As per GeM Category Specification](#)

Specification	Specification Name	Bid Requirement (Allowed Values)
MATERIAL	<b>Type of material (other than wood) used in Polythene cane Chair</b>	NOT APPLICABLE
	<b>Material of Fabric Back Cover</b>	leather foam, leatherite
	Thickness of Plywood used in Backrest IN MM ( $\pm 1$ mm)	18 mm
	<b>Frame Material</b>	chrome on MS
	Density of Polyurethane Foam Used in Seat $\pm 2$ (Kg/Cub M)	40 Kg/Cub.M
	<b>Material of Fabric of Seat Cover</b>	black leatherite
	Density of Polyurethane Foam Used in Backrest $\pm 2$ (Kg/Cub M)	40 Kg/Cub.M

	<b>Thickness of Plywood used in Seat ±1(mm)</b>	12 mm
	<b>GSM/Thickness of Fabric ±5 (Gram per Sq Meter)</b>	250 Gram per Sq Meter, N.A
	<b>Arm Material</b>	chrome mild steel, Padded Cushion Upholsted With Leather On Metal
	<b>Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 3 mm)</b>	50 mm
	<b>Thickness of Polyurethane Foam Used in Seat IN MM (+/- 3 mm)</b>	40 mm
	Shoe Type	nylon rubber
GENERIC	<b>Chair Type</b>	With Arms
	<b>Type of Seat and Backrest</b>	Padded with Polyurethane Foam
	<b>Frame Type</b>	Cantilever
	<b>Castors</b>	Without
DIMENSION	<b>Size of Material (mm)</b>	16 SWG 30 mm round pipe, 16 gauge tubular pipe
	<b>Chair Height ±15(mm)</b>	1000 mm
	<b>Seat Depth ±10(mm)</b>	550 mm
	<b>Seat Width ±10 (mm)</b>	550 mm
	<b>Seat Height IN MM ±5(mm)</b>	480
	<b>Backrest Width ±10(mm)</b>	550 mm
	<b>Backrest Height ±10(mm)</b>	550 mm, 600 mm
	<b>Arm Length ±5(mm)</b>	400 mm, N.A
	<b>Arm Width ±2(mm)</b>	75 mm, N.A
COLOUR & FINISH	Colour of Fabric for Seat and Backrest	black, N.A
	<b>Paint Type</b>	chrome
	Colour of Paint	NA
CERTIFICATION	Polythene cane conforming to Type-1 of IS 5378 /1994	NA
	<b>Test reports to be furnished to buyer on demand</b>	YES
	<b>BIFMA certification</b>	NO
	<b>OEM of offered product is ISO 9001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 14001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 18001:2007 certified</b>	NO
WARRANTY	<b>Warranty period in number of years</b>	1, 3

**Consignees/Reporting Officer and Quantity**

S.No.	Consignee/Reporting	Address	Delivery Schedule (In number of days from
-------	---------------------	---------	---

	Officer		contract start days)		
1	K B R Deepti	508126,Bibinagar	Quantity	Delivery to start after	Delivery to be completed by
			30	25	35

## Sofas ( 15 pieces )

### Technical Specifications

\* As per GeM Category Specification

Specification	Specification Name	Bid Requirement (Allowed Values)
Material	<b>Frame Structure Material and size (<math>\pm 1</math> mm)</b>	18 mm teak plywood
	<b>Seat Cushion Material</b>	foam
	Density of Cushion of Seat Material $\pm 3$ (Kg/Cubic M)	40
	<b>Type of Spring in the Base / Seating</b>	eight way hand tied spring
Generic	<b>Total Number of Seats in the Sofa Set (Nos)</b>	5
	Type of Sofa and Backrest	Seat and Backrest are permanently fixed with the frame Structure
	<b>Number of Single Seater Units (Nos)</b>	2
	<b>Number of Two Seater Units (Nos)</b>	NO TWO SEATER UNIT
	<b>Number of Three Seater Units (Nos)</b>	1
	<b>Number of Four Seater Units (Nos)</b>	NO FOUR SEATER UNITS
	<b>Frame Covering</b>	Partially Upholstered
	<b>Sofa Set is Foldable to use as bed</b>	Yes, No
	Backrest Cushion Material	foam
	Density of Cushion of Backrest Material (Kg/Cubic M)	40, 45, 50, 55, 60, 65, 70, 75 Or higher
<b>Covering Material for Seat and Backrest</b>	rexin	
Dimension	<b>Length of Single Seater Units in mm (<math>\pm 5</math> mm)</b>	508
	<b>Length of Two Seater Units in mm (<math>\pm 10</math> mm)</b>	N.A
	<b>Length of Three Seater Units in mm (<math>\pm 10</math> mm)</b>	1200
	<b>Length of Four Seater Units in mm (<math>\pm 10</math> mm)</b>	N.A
	<b>Depth of Sofa Units in mm (<math>\pm 10</math> mm)</b>	457
	<b>Sofa Height (Without Back Cushion) <math>\pm 5</math> (mm)</b>	400.0

	<b>Sofa Height (With Back Cushion) ±5 mm</b>	600.0
	Arm Width ±5 (mm)	100.0
	Arm Height ±5 (mm)	400.0
	Seat Height (With Seat Cushion) ±5 (mm)	400.0
	Sofa Leg Height ±2(mm)	25.0
	Sofa Leg Width / Diameter ±2 (mm)	50.0
	<b>Seat Cushion Length ±5 (mm)</b>	710
	<b>Seat Cushion Width ±5 (mm)</b>	NA
	<b>Seat Cushion Thickness ±5 (mm)</b>	NA
	<b>Backrest Cushion Length ±5 (mm)</b>	710
	<b>Backrest Cushion Width ±5 (mm)</b>	NA
	Backrest Cushion Thickness ±3 (mm)	100
	Thickness of Foam in arms ±2 (mm)	50
	Thickness of Foam in back ±2 (mm)	76.0
	Thickness of Foam in front ±2 (mm)	76.0
	Thickness of Foam in sides ±2 (mm)	76.0
Colour & Finish	Colour of Polish on exposed Wood frame	N.A
	Colour of Covering Material	AS PER BUYER'S CHOICE
Warranty	<b>WARRANTY PERIOD IN NUMBER OF YEARS</b>	1

**Consignees/Reporting Officer and Quantity**

S.No.	Consignee/Reporting Officer	Address	Delivery Schedule (In number of days from contract start days)		
			Quantity	Delivery to start after	Delivery to be completed by
1	K B R Deepti	508126,Bibinagar	15	30	40

**Centre Table ( 15 pieces )**

**Technical Specifications**

[\\* As per GeM Category Specification](#)

Specification	Specification Name	Bid Requirement (Allowed Values)

GENERIC	Mode of supply	Assembled ready to use
	Shape of the Centre table	Rectangular
	Style of Centre Table	Supported by set of Legs
	Design of centre table	With four legs only
	<b>Number of storage under top</b>	Single storage in bottom portion
MATERIAL	<b>Top material</b>	Flat glass
	<b>Frame material</b>	Carved Teak wood
	Leg material	Teak carved wood
	Material of Understructure supporting the top	Other wood
	Storage material	Other wood
	Shoes Material	No shoes
DIMENSION & THICKNESS	<b>Dimension of Top (length X Breadth) ±20mm</b>	914mmX609mm
	<b>Height of centre table ±10 mm</b>	430.0
	<b>Thickness of top material (+/-2 mm)</b>	12.0
	<b>Thickness of frame material (+/- 1 mm)</b>	19.0
	Thickness of leg material	35mm X 35mm
	Thickness of understructure support material	18.0
MISC	connecting of leg	Adjacent side of leg
	Number of buffers	No buffers
COLOUR & FINISH	Table top finish	Teak laminate/ply with polish
WARRANTY	<b>Warranty period in number of years</b>	2
CERTIFICATION	Test reports to be furnished to buyer on demand	NO
	Product having BIFMA certification	NO
	OEM of offered product is ISO 9001:2015 certified	NO
	OEM of offered product is ISO 14001:2015 certified	NO
	OEM of offered product is ISO 18001:2007 certified	NO

**Additional Specification Parameters - Centre Table ( 15 pieces )**

Specification Parameter Name	Bid Requirement (Allowed Values)
Shoe Material	Nylon rubber

\* Bidders offering must also comply with the additional specification parameters mentioned above.

**Consignees/Reporting Officer and Quantity**

S.No.	Consignee/Reporting	Address	Delivery Schedule (In number of days from
-------	---------------------	---------	---



	Officer		contract start days)		
1	K B R Deepti	508126,Bibinagar	Quantity	Delivery to start after	Delivery to be completed by
			15	30	40

### Executive Table ( 120 pieces )

#### Technical Specifications

\* As per GeM Category Specification

Specification	Specification Name	Bid Requirement (Allowed Values)
MATERIAL	<b>Table top Material</b>	Commercial Block Board BWP grade Conforming to IS 1659
	<b>Gable end and modesty panel material</b>	Commercial Block Board BWP grade Conforming to IS 1659
	<b>Leg Material</b>	NO LEGS
GENERIC	<b>Mode of supply</b>	Assembled Ready To Use
	Understructure of table	Gable end and modesty panel
	<b>Storage provided</b>	One side, Both side
	<b>Keyboard tray</b>	Not provided
	<b>Foot rest</b>	Provided
MISC	Table top plain sides	Edge to be banded with PVC tape of 2mm thick with the help of hot melt glue, CP Teak Wood Lipping
	Gable end and modesty panel plain side	Edge to be banded with PVC tape of 2mm thick with the help of hot melt glue, N.A
DIMENSION	<b>Thickness of table top <math>\pm 2</math> mm</b>	19.0
	Thickness of gable end and modesty panel $\pm 2$ mm	19.0, 15.0
	<b>Length of table top <math>\pm 10</math> mm</b>	2100.0
	<b>Depth of table <math>\pm 10</math> mm</b>	950.0
	<b>Height of table <math>\pm 10</math> mm</b>	750.0
	<b>Dimension of leg(mmXmm) <math>\pm 5</math>mm</b>	No legs
STORAGE UNIT	<b>Number of Storage unit provided</b>	Single storage, Triple storage
	Width of storage unit $\pm 10$ mm	400mm
	Depth of storage unit in mm ( $\pm 10$ mm)	650
	Height of smallest storage unit $\pm 5$ mm	100mm, N.A
	Height of medium storage unit $\pm 5$ mm	N.A
	Height of largest storage unit $\pm 5$ mm	N.A
KEYBOARD TRAY	Type of keyboard tray	N.A
	Material of keyboard tray and Right angle L-type supporting bracket	N.A

	Keyboard adjustability	N.A
	fixing of supporting bracket	N.A
	Length of telescopic channel $\pm 10$ mm	400mm, N.A
	Average weight of telescopic channel $\pm 50$ Gms	600Gms per set, N.A
	Keyboard front width $\pm 10$ mm	N.A
	Keyboard depth $\pm 10$ mm	N.A
	Keyboard height $\pm 10$ mm	N.A
	Finish of exposed edges of keyboard tray	N.A
	Material thickness of keyboard tray $\pm 1$ mm	N.A
FOOTREST	Material of footrest	Commercial Block Board BWP grade Conforming to IS 1659
	Length of footrest $\pm 10$ mm	N.A
	Depth of footrest $\pm 10$ mm	N.A
	Height of footrest $\pm 10$ mm	N.A
	Finish of exposed edges	To be banded with 0.5-1.0mm thick PVC tape with the help of hot melt glue, N.A
	<b>Material thickness of footrest <math>\pm 2</math>mm</b>	19mm
COLOUR & FINISH	Table top finish	Teak laminate/ply with polish
	Table top shade	As per Buyer's choice
WARRANTY	<b>Warrantee period in number of years</b>	1
CERTIFICATION	Test reports to be furnished to buyer on demand	NO
	<b>Product having BIFMA certification</b>	NO
	<b>OEM of offered product is ISO 9001:2015 certified</b>	YES
	<b>OEM of offered product is ISO 14001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 18001:2007 certified</b>	NO

**Additional Specification Parameters - Executive Table ( 120 pieces )**

Specification Parameter Name	Bid Requirement (Allowed Values)
Table to fixed with	Gable end and Modesty panel using Minifix and Wooden dowel by using (knock down) system for interconnecting
For Gap/Wrapage	Number of Minifix/Dowel can be modified (One in 1000mm length, Two in 1001 to 2000mm, Three in above 2000mm length) made of 1.2mm thick CRC sheet duly galvanized/Powder coated.
Number of buffers to be provided	4 numbers at bottom
Lock provided	yes

\* Bidders offering must also comply with the additional specification parameters mentioned above.

**Consignees/Reporting Officer and Quantity**

S.No.	Consignee/Reporting Officer	Address	Delivery Schedule (In number of days from contract start days)		
1	K B R Deepti	508126,Bibinagar	Quantity	Delivery to start after	Delivery to be completed by
			60	25	30
			60	30	40

**Chairs-Office- IS 3499 ( 310 pieces )**

**Technical Specifications**

[\\* As per GeM Category Specification](#)

Specification	Specification Name	Bid Requirement (Allowed Values)
MATERIAL	<b>Type of material (other than wood) used in Polythene cane Chair</b>	NOT APPLICABLE
	<b>Material of Fabric Back Cover</b>	leather foam, leatherite
	Thickness of Plywood used in Backrest IN MM ( $\pm 1$ mm)	N.A
	<b>Frame Material</b>	chrome on MS
	Density of Polyurethane Foam Used in Seat $\pm 2$ (Kg/Cub M)	32 Kg/Cub.M
	<b>Material of Fabric of Seat Cover</b>	black leatherite
	Density of Polyurethane Foam Used in Backrest $\pm 2$ (Kg/Cub M)	32 Kg/Cub.M
	<b>Thickness of Plywood used in Seat <math>\pm 1</math>(mm)</b>	N.A
	<b>GSM/Thickness of Fabric <math>\pm 5</math> (Gram per Sq Meter)</b>	N.A
	<b>Arm Material</b>	wooden
	<b>Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 3 mm)</b>	25 mm
	<b>Thickness of Polyurethane Foam Used in Seat IN MM (+/- 3 mm)</b>	20 mm
	Shoe Type	PVC
GENERIC	<b>Chair Type</b>	With Arms
	<b>Type of Seat and Backrest</b>	Made of Polythene cane
	<b>Frame Type</b>	4 Legs
	<b>Castors</b>	Without
DIMENSION	<b>Size of Material (mm)</b>	2 mm thick 25 mm tube
	<b>Chair Height <math>\pm 15</math>(mm)</b>	800 mm
	<b>Seat Depth <math>\pm 10</math>(mm)</b>	400 mm

	<b>Seat Width ±10 (mm)</b>	380 mm
	<b>Seat Height IN MM ±5(mm)</b>	400
	<b>Backrest Width ±10(mm)</b>	350 mm
	<b>Backrest Height ±10(mm)</b>	350 mm
	<b>Arm Length ±5(mm)</b>	200 mm
	<b>Arm Width ±2(mm)</b>	40 mm
COLOUR & FINISH	Colour of Fabric for Seat and Backrest	black
	<b>Paint Type</b>	powder coated on MS
	Colour of Paint	black
CERTIFICATION	Polythene cane conforming to Type-1 of IS 5378 /1994	NO
	<b>Test reports to be furnished to buyer on demand</b>	NO
	<b>BIFMA certification</b>	NO
	<b>OEM of offered product is ISO 9001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 14001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 18001:2007 certified</b>	NO
WARRANTY	<b>Warranty period in number of years</b>	4

#### Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Delivery Schedule (In number of days from contract start days)		
			Quantity	Delivery to start after	Delivery to be completed by
1	K B R Deepti	508126,Bibinagar			
			150	25	30
			160	30	40

#### Revolving Chair ( 120 pieces )

##### Technical Specifications

\* As per GeM Category Specification

Specification	Specification Name	Bid Requirement (Allowed Values)
MATERIAL	<b>Pedestal Base</b>	Glass Fibre Nylon with ABS/ NylonTwin Caster Wheels Minimum 5 Nos, of 50 mm Size
	<b>Arm Material</b>	Proppylene
	<b>seat material</b>	PU foam covered with mesh fabric
	Density of PU foam used in seat KG per Cu Meter (+/- 3)	35
	Density of PU foam used in	35

	backrest in KG per Cu Meter (+/- 3)	
	<b>Material of Fabric Back Cover / Material for Backrest</b>	mesh fabric
	<b>Material of Fabric of Seat Cover</b>	Mesh Fabrics
	GSM/Thickness of fabric ±5%(Gram/Square meter)	220 gram
GENERAL	<b>Chair Type</b>	central tilt
	Tilt Tension Adjustment	Yes
	<b>Height Adjustment ± 5(mm)</b>	up to 100 mm
	<b>Arm</b>	With
	<b>Type of backrest support</b>	backrest symmetrical lumber support
	<b>Arm Type</b>	Adjustable
	Colour of Fabric for Seat and Backrest	black
	<b>Ergonomic Seat Design</b>	Yes
	<b>Back type</b>	push back
	Backrest is made of two pcs injection moulded frame	Backrest is made of two pcs injection moulded frame
	<b>backrest has separate adjustable headrest</b>	Yes
	<b>Seat type</b>	fixed
	Type of locking	N.A
	<b>Number of arm movement</b>	N.A
<b>Lumber support</b>	N.A	
DIMENSION	<b>Overall Chair Height ±15mm</b>	1250
	<b>Backrest Height ±15mm</b>	800.0
	<b>Backrest Width ±10mm</b>	480.0
	<b>Seat Height ±15 mm</b>	520
	<b>Seat Width ±10 mm</b>	480
	<b>Seat Depth ±10 mm</b>	520.0
	<b>Thickness of MS Plate Joining the under structure with Seat</b>	0.2
	<b>Thickness of Plywood used in Seat ±1(mm)</b>	12 mm
	<b>Thickness of Plywood used in Backrest ± 1(mm)</b>	N.A
	Padestal Size (Diameter in mm) +/- 10 mm	580
	<b>Thickness of Polyurethane Foam Used in Seat in mm (+/- 2 mm)</b>	50 mm
	<b>Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 2 MM)</b>	N.A
WARANTEE	<b>Warrantee period in number of years</b>	1-year

CERTIFICATION	<b>Test reports to be furnished to buyer on demand</b>	NO
	<b>BIFMA Certification</b>	NO
	<b>OEM of offered product is ISO 9001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 14001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 18001:2007 certified</b>	NO
	<b>Green guard certification</b>	NO
	<b>Aiota</b>	NO

#### Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Delivery Schedule (In number of days from contract start days)		
			Quantity	Delivery to start after	Delivery to be completed by
1	K B R Deepti	508126,Bibinagar	60	25	30
			60	30	40

#### Revolving Chair ( 270 pieces )

##### Technical Specifications

\* [As per GeM Category Specification](#)

Specification	Specification Name	Bid Requirement (Allowed Values)
MATERIAL	<b>Pedestal Base</b>	ABS Plastic with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size
	<b>Arm Material</b>	Proppylene
	<b>seat material</b>	PU Foam covered with Fabric
	Density of PU foam used in seat KG per Cu Meter (+/- 3)	32
	Density of PU foam used in backrest in KG per Cu Meter (+/- 3)	32
	<b>Material of Fabric Back Cover / Material for Backrest</b>	100% polyester fabric
	<b>Material of Fabric of Seat Cover</b>	100% polyester fabric
	GSM/Thickness of fabric $\pm 5\%$ (Gram/Square meter)	N.A
GENERAL	<b>Chair Type</b>	push back
	Tilt Tension Adjustment	Yes, No
	<b>Height Adjustment <math>\pm 5</math>(mm)</b>	up to 90 mm
	<b>Arm</b>	With

	<b>Type of backrest support</b>	backrest symmetrical lumber support
	<b>Arm Type</b>	Fixed
	Colour of Fabric for Seat and Backrest	BLUE
	<b>Ergonomic Seat Design</b>	Yes
	<b>Back type</b>	push back
	Backrest is made of two pcs injection moulded frame	Backrest is made of one piece injection moulded frame
	<b>backrest has separate adjustable headrest</b>	Yes, No
	<b>Seat type</b>	sliding
	Type of locking	upright locking
	<b>Number of arm movement</b>	N.A
	<b>Lumber support</b>	N.A
DIMENSION	<b>Overall Chair Height ±15mm</b>	950
	<b>Backrest Height ±15mm</b>	500.0
	<b>Backrest Width ±10mm</b>	480.0
	<b>Seat Height ±15 mm</b>	480, 500
	<b>Seat Width ±10 mm</b>	500
	<b>Seat Depth ±10 mm</b>	480.0
	<b>Thickness of MS Plate Joining the under structure with Seat</b>	0.0
	<b>Thickness of Plywood used in Seat ±1(mm)</b>	N.A
	<b>Thickness of Plywood used in Backrest ± 1(mm)</b>	N.A
	Padestal Size (Diameter in mm) +/- 10 mm	580
	<b>Thickness of Polyurethane Foam Used in Seat in mm (+/- 2 mm)</b>	25 mm
	<b>Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 2 MM)</b>	25 mm
	WARANTEE	<b>Warrantee period in number of years</b>
CERTIFICATION	<b>Test reports to be furnished to buyer on demand</b>	NO
	<b>BIFMA Certification</b>	NO
	<b>OEM of offered product is ISO 9001:2015 certified</b>	YES
	<b>OEM of offered product is ISO 14001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 18001:2007 certified</b>	NO
	<b>Green guard certification</b>	NO
	<b>Aiota</b>	NO

**Consignees/Reporting Officer and Quantity**

S.No.	Consignee/Reporting Officer	Address	Delivery Schedule (In number of days from contract start days)		
1	K B R Deepti	508126,Bibinagar	Quantity	Delivery to start after	Delivery to be completed by
			120	25	30
			150	30	40

**Executive Table ( 250 pieces )**

**Technical Specifications**

\* As per GeM Category Specification

Specification	Specification Name	Bid Requirement (Allowed Values)
MATERIAL	<b>Table top Material</b>	Three layer prelaminated particle board(Wood Product) of grade II type II of IS 12823/Latest
	<b>Gable end and modesty panel material</b>	Three Layer prelaminated particles board(wood product) of grade II type III of IS 12823/Latest
	<b>Leg Material</b>	NO LEGS
GENERIC	<b>Mode of supply</b>	Knocked Down To Be Assembled At Consignee Site By The Seller
	Understructure of table	Gable end and modesty panel
	<b>Storage provided</b>	One side
	<b>Keyboard tray</b>	Not provided
	<b>Foot rest</b>	Not Provided
MISC	Table top plain sides	Edge to be banded with PVC tape of 2mm thick with the help of hot melt glue
	Gable end and modesty panel plain side	Edge to be banded with PVC tape of 2mm thick with the help of hot melt glue
DIMENSION	<b>Thickness of table top <math>\pm 2</math> mm</b>	19.0
	Thickness of gable end and modesty panel $\pm 2$ mm	19.0
	<b>Length of table top <math>\pm 10</math> mm</b>	1500.0
	<b>Depth of table <math>\pm 10</math> mm</b>	750.0
	<b>Height of table <math>\pm 10</math> mm</b>	750.0
	<b>Dimension of leg(mmXmm) <math>\pm 5</math>mm</b>	No legs
STORAGE UNIT	<b>Number of Storage unit provided</b>	Single storage
	Width of storage unit $\pm 10$ mm	400mm
	Depth of storage unit in mm ( $\pm 10$ mm)	700, NA
	Height of smallest storage unit $\pm 5$ mm	N.A
	Height of medium storage unit $\pm 5$ mm	N.A



	Height of largest storage unit ±5mm	N.A
KEYBOARD TRAY	Type of keyboard tray	N.A
	Material of keyboard tray and Right angle L-type supporting bracket	N.A
	Keyboard adjustability	N.A
	fixing of supporting bracket	N.A
	Length of telescopic channe±10mm	400mm, N.A
	Average weight of telescopic channel ±50Gms	600Gms per set, N.A
	Keyboard front width±10mm	N.A
	Keyboard depth±10mm	N.A
	Keyboard height±10mm	N.A
	Finish of exposed edges of keyboard tray	N.A
	Material thickness of keyboard tray ±1mm	N.A
FOOTREST	Material of footrest	N.A
	Length of footrest ±10mm	N.A
	Depth of footrest ±10mm	N.A
	Height of footrest ±10mm	N.A
	Finish of exposed edges	N.A
	<b>Material thickness of footrest ±2mm</b>	N.A
COLOUR & FINISH	Table top finish	Laminate in colour with swede finish 0.6-0.8mm thickness of type S,F or P having index no.3.2.3 conforming to IS 2046/Latest with having balancing laminate of 0.5mm thick on other side, Laminate in colour with matt finish 0.6-0.8mm thickness of type S,F or P having index no.3.2.3 conforming to IS 2046/Latest with having balancing laminate of 0.5mm thick on other side
	Table top shade	Oak, As per Buyer's choice
WARRANTY	<b>Warrantee period in number of years</b>	1
CERTIFICATION	Test reports to be furnished to buyer on demand	YES
	<b>Product having BIFMA certification</b>	YES, NO
	<b>OEM of offered product is ISO 9001:2015 certified</b>	YES
	<b>OEM of offered product is ISO 14001:2015 certified</b>	YES
	<b>OEM of offered product is ISO 18001:2007 certified</b>	YES

**Additional Specification Parameters - Executive Table ( 250 pieces )**

Specification Parameter Name	Bid Requirement (Allowed Values)
Number of buffers to be provided	4 numbers at bottom

Table top long side	To be post form half round profile
---------------------	------------------------------------

\* Bidders offering must also comply with the additional specification parameters mentioned above.

### Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Delivery Schedule (In number of days from contract start days)		
			Quantity	Delivery to start after	Delivery to be completed by
1	K B R Deepti	508126,Bibinagar	100	25	30
			150	30	40

### Chairs-Office- IS 3499 ( 200 pieces )

#### Technical Specifications

[\\* As per GeM Category Specification](#)

Specification	Specification Name	Bid Requirement (Allowed Values)
MATERIAL	<b>Type of material (other than wood) used in Polythene cane Chair</b>	hot pressed board
	<b>Material of Fabric Back Cover</b>	N.A
	Thickness of Plywood used in Backrest IN MM ( $\pm 1$ mm)	18 mm
	<b>Frame Material</b>	chrome on MS
	Density of Polyurethane Foam Used in Seat $\pm 2$ (Kg/Cub M)	N.A
	<b>Material of Fabric of Seat Cover</b>	fabric
	Density of Polyurethane Foam Used in Backrest $\pm 2$ (Kg/Cub M)	N.A
	<b>Thickness of Plywood used in Seat <math>\pm 1</math>(mm)</b>	18 mm
	<b>GSM/Thickness of Fabric <math>\pm 5</math> (Gram per Sq Meter)</b>	N.A
	<b>Arm Material</b>	fiber
	<b>Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 3 mm)</b>	50 mm
	<b>Thickness of Polyurethane Foam Used in Seat IN MM (+/- 3 mm)</b>	20 mm
	Shoe Type	plastic
GENERIC	<b>Chair Type</b>	With Arms
	<b>Type of Seat and Backrest</b>	Padded with Polyurethane Foam
	<b>Frame Type</b>	Cantilever
	<b>Castors</b>	Without

DIMENSION	<b>Size of Material (mm)</b>	16 SWG 30 mm round pipe
	<b>Chair Height ±15(mm)</b>	850 mm
	<b>Seat Depth ±10(mm)</b>	450 mm
	<b>Seat Width ±10 (mm)</b>	400 mm
	<b>Seat Height IN MM ±5(mm)</b>	480
	<b>Backrest Width ±10(mm)</b>	400 mm
	<b>Backrest Height ±10(mm)</b>	450 mm
	<b>Arm Length ±5(mm)</b>	300 mm
	<b>Arm Width ±2(mm)</b>	50 mm
COLOUR & FINISH	Colour of Fabric for Seat and Backrest	N.A
	<b>Paint Type</b>	chrome
	Colour of Paint	black
CERTIFICATION	Polythene cane conforming to Type-1 of IS 5378 /1994	NA
	<b>Test reports to be furnished to buyer on demand</b>	YES
	<b>BIFMA certification</b>	YES
	<b>OEM of offered product is ISO 9001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 14001:2015 certified</b>	NO
	<b>OEM of offered product is ISO 18001:2007 certified</b>	NO
WARRANTY	<b>Warranty period in number of years</b>	1

**Additional Specification Parameters - Chairs-Office- IS 3499 ( 200 pieces )**

Specification Parameter Name	Bid Requirement (Allowed Values)
Conformity to Indian Standard IS 3499 (Part-I) Latest	Yes

\* Bidders offering must also comply with the additional specification parameters mentioned above.

**Consignees/Reporting Officer and Quantity**

S.No.	Consignee/Reporting Officer	Address	Delivery Schedule (In number of days from contract start days)		
			Quantity	Delivery to start after	Delivery to be completed by
1	K B R Deepti	508126,Bibinagar			
			100	25	30
			100	30	40

**Bid Specific Additional Terms and Conditions**

- 1.Authorised Service Centre within the state of Odisha, along with a dedicated contact person with telephone number for technical solution in a fast track basis at this institution as and when required basis.
- 2.Experience Certificate for the supply of the same to any Govt/ PSU/ any renowned private organisation along with Supply/ Purchase Order.

- 3.If the agency is registered under MSME or NSIC, then EMD exemption certificate needs to be enclosed.
- 4.Make in india specific authorisation certificate needs to be enclosed.
- 5.After award of contract – Successful Bidder shall have to get Detailed Design Drawings approved from buyer before starting fabrication. Successful Bidder shall submit Detailed Design Drawings for Buyer's approval, within 5 days of award of contract. Buyer shall, either approve the drawings or will provide complete list of modification required in the drawings within 5 days. Seller shall be required to ensure supply as per approved Drawings with modifications as communicated by Buyer. If there is delay from buyer side in approval of drawing- the delivery period shall be refixed without LD for the period of delay in approval of Drawing.
- 6.Actual delivery (and Installation & Commissioning (if covered in scope of supply)) is to be done at following address K.B.R. Deepti, Manager (Civil), Engineer In-charge (EIC), HITES Second Floor, All India Institute of Medical Science (AIIMS), Bibinagar Yadadri, Bhongiri District Telangana-508126.
- 7.**Bidder financial standing:** The bidder should not be under liquidation, court receivership or similar proceedings, should not be bankrupt. Bidder to upload undertaking to this effect with bid.
- 8.Bidders are advised to check applicable GST on their own before quoting. Buyer will not take any responsibility in this regards. GST reimbursement will be as per actuals or as per applicable rates (whichever is lower), subject to the maximum of quoted GST %.
- 9.**End User Certificate:** Wherever Bidders are insisting for End User Certificate from the Buyer, same shall be provided in Buyer's standard format only.
- 10.Experience Criteria: The Bidder or its OEM {themselves or through reseller(s)} should have regularly, manufactured and supplied same or similar Category Products to any Central / State Govt Organization / PSU / Public Listed Company for 3 years before the bid opening date. Copies of relevant contracts to be submitted along with bid in support of having supplied some quantity during each of the year. In case of bunch bids, the primary product having highest value should meet this criterion.
- 11.For hazardous chemical/item, all precautionary measure as per regulation from the point of transportation/ handling/ storage/ safety/ health/ environment to be undertaken/ specified before dispatch. During dispatch, proper symbol for the hazard/ MSDS/ Batch No./ date of manufacturing/ Gross Weight/ Net Weight/ shelf Life etc are to be written/ printed/ pasted on the body of the packing.
- 12.Installation, Commissioning, Testing, Configuration, Training (if any - which ever is applicable as per scope of supply) is to be carried out by OEM / OEM Certified resource or OEM authorised Reseller.
- 13.OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity by up to 25% of the contracted quantity during the currency of the contract at the contracted rates. Bidders are bound to accept the orders accordingly.
- 14.**OPTIONAL SITE VISIT:**
  1. The Bidder is advised to visit and examine the installation site and its surroundings and obtain for itself on its own responsibility all information that may be necessary for preparing the Bid. The costs of visiting the site shall be borne by the Bidder. At bidders own risk and cost
  2. The Bidder representative shall be allowed entry upon consignee premises for such visits, only upon the express conditions that the Bidder will release and indemnify the Buyer and Consignee against all liabilities arising out of such visit including death or injury, loss or damage to property, and any other loss, damage, costs, and expenses incurred as a result of such visit.
  3. The Bidder shall not be entitled to hold any claim against Buyer for noncompliance due to lack of any kind of pre-requisite information as it is the sole responsibility of the Bidder to obtain all the necessary information with regard to site, surrounding, working conditions, weather etc. on its own before submission of the bid.
- 15.Scope of supply includes Training: Number of employees to be trained 3 , Place for Training All India Institute of Medical Science (AIIMS), Bibinagar and Duration of training 3 days.
- 16.Supplier shall ensure that the Invoice is raised in the name of Consignee with GSTIN of Consignee only.
- 17.**Shelf Life:** The Product to be supplied must have minimum 5 Years Shelf Life. On the date of supply, minimum 5 Years and 3 Months usable shelf life should be available / balance.
- 18.The successful bidder has to supply all essential accessories required for the successful installation and commissioning of the goods supplied. Besides standard accessories as per normal industry practice, following accessories must be part of supply and cost should be included in bid price: As per the terms of contract.
- 19.1. The Seller shall not assign the Contract in whole or part without obtaining the prior written consent of buyer.  
2. The Seller shall not sub-contract the Contract in whole or part to any entity without obtaining the prior written consent of buyer.  
3. The Seller shall, notwithstanding the consent and assignment/sub-contract, remain jointly and severally liable and responsible to buyer together with the assignee/ sub-contractor, for and in respect of the due performance of the Contract and the Sellers obligations there under.
- 20.The seller is required to print logo as per buyer's requirement.
- 21.**Upload Manufacturer authorization:** Wherever Authorised Distributors are submitting the bid, Manufacturers Authorisation Form (MAF)/Certificate with OEM details such as name, designation, address, e-mail Id and Phone No. required to be furnished along with the bid.
- 22.While generating invoice in GeM portal, the seller must upload scanned copy of GST invoice and the screenshot of GST portal confirming payment of GST.

23. **IMPORTED PRODUCTS:** In case of imported products, OEM or Authorized Seller of OEM should have a registered office in India to provide after sales service support in India. The certificate to this effect should be submitted.
24. **Nominated Inspection Agency:** On behalf of the Buyer organization, any one of the following Inspection Agency would be conducting inspection of stores before acceptance:  
Pre-dispatch Inspection at Seller Premises (applicable only if pre-dispatch inspection clause has been selected in ATC): Not applicable  
Post Receipt Inspection at consignee site before acceptance of stores: At Consignee Site (AIIMS, Bibinagar, Telangana) by Board of Officers
25. After award of contract – Successful Bidder shall have to get advance sample approved from buyer before bulk manufacturing / starting bulk supplies. Successful Bidder shall submit 3 samples for Buyer's approval, within 5 days of award of contract. Buyer shall, as per contract specifications framework, either approve the advance sample or will provide complete list of modification required in the sample within 5 days of receipt of advance sample. Seller shall be required to ensure supply as per approved sample with modifications as communicated by Buyer. If there is delay from buyer side in approval of advance sample – the delivery period shall be refixed without LD for the period of delay in sample approval. In case, the sample is found to have major deviations / not conforming to the Contract specifications, the buyer at its discretion may call for fresh samples for approval before allowing bulk supplies or may terminate the contract after notifying the deviations to the seller. Unless otherwise provided in the contract, all samples required for test shall be supplied by the contractor free of cost. Where under the contract, the contractor is required to submit an advance sample, any expenses incurred by the contractor on or in connection with the production of stores in bulk, before the sample has been approved unconditionally shall be borne by the Seller and he shall not claim any compensation in the event of such sample being found unacceptable by the Buyer / Consignee.
26. Bidders can also submit the EMD with Payment online through RTGS / internet banking in Beneficiary name HLL Infratech Services Limited Account No. 38160968975 IFSC Code SBIN0004350 Bank Name State Bank of India Branch address Commercial Branch, Trivandrum.  
Bidder to indicate bid number and name of bidding entity in the transaction details field at the time of on-line transfer. Bidder has to upload scanned copy / proof of the Online Payment Transfer along with bid.
27. Successful Bidder can submit the Performance Security in the form of Payment online through RTGS / internet banking also (besides PBG which is allowed as per GeM GTC). On-line payment shall be in Beneficiary name HLL Infratech Services Limited Account No. 38160968975 IFSC Code SBIN0004350 Bank Name State Bank of India Branch address Commercial Branch, Trivandrum. Successful Bidder to indicate Contract number and name of Seller entity in the transaction details field at the time of on-line transfer. Bidder has to upload scanned copy / proof of the Online Payment Transfer in place of PBG within 15 days of award of contract.
28. **NET WORTH:** Net Worth of the OEM should be positive as per the last audited financial statement.
29. Bidder's offer is liable to be rejected if they don't upload any of the certificates / documents sought in the Bid document, ATC and Corrigendum if any.
30. ISO 9001: The bidder or the OEM of the offered products must have ISO 9001 certification.
31. Material Test Certificate Should Be Sent Along with The Supply. The Material Will Be Checked by Buyer's Lab & the Results of the Lab will be the Sole Criteria for Acceptance of the Item.
32. The bidder is required to upload, along with the bid, all relevant certificates such as BIS licence, type test certificate, approval certificates and other certificates as prescribed in the Product Specification given in the bid document.
33. To be eligible for award of contract, Bidder / OEM must possess following Certificates / Test Reports on the date of bid opening (to be uploaded with bid): BIFMA, Green Building Certificate and Mandatory Test certificate.
34. Bidder Turn Over Criteria: The minimum average annual financial turnover of the bidder during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the bidder is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria.
35. OEM Turn Over Criteria: The minimum average annual financial turnover of the OEM of the offered product during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the OEM is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria. In case of bunch bids, the OEM of CATEGORY RELATED TO primary product having highest bid value should meet this criterion.
36. Availability of Service Centres: Bidder/OEM must have a Functional Service Centre in the State of each Consignee's Location in case of carry-in warranty. (Not applicable in case of goods having on-site warranty). If service center is not already there at the time of bidding, successful bidder / OEM shall have to establish one within 30 days of award of contract. Payment shall be released only after submission of documentary evidence of having Functional Service Centre.
37. Dedicated /toll Free Telephone No. for Service Support : BIDDER/OEM must have Dedicated/toll Free Telephone No. for Service Support.
38. Successful bidder will have to ensure that adequate number of dedicated technical service personals / engineers are designated / deployed for attending to the Service Request in a time bound manner and for ensuring Timely

Servicing / rectification of defects during warranty period, as per Service level agreement indicated in the relevant clause of the bid.

39. Timely Servicing / rectification of defects during warranty period: After having been notified of the defects / service requirement during warranty period, Seller has to complete the required Service / Rectification within 3 days time limit. If the Seller fails to complete service / rectification with defined time limit, a penalty of 0.5% of Unit Price of the product shall be charged as penalty for each week of delay from the seller. Seller can deposit the penalty with the Buyer directly else the Buyer shall have a right to recover all such penalty amount from the Performance Security (PBG). Cumulative Penalty cannot exceed more than 10% of the total contract value after which the Buyer shall have the right to get the service / rectification done from alternate sources at the risk and cost of the Seller besides forfeiture of PBG. Seller shall be liable to re-imburse the cost of such service / rectification to the Buyer.
40. For fulfilling the experience criteria any one of the following documents may be considered as valid proof for meeting the experience criteria:
- Purchase Order copy along with Invoice(s) with self-certification by the bidder that supplies against the invoices have been executed.
  - Execution certificate by client with order value.
  - Any other document in support of order execution like Third Party Inspection release note, etc.
41. The Bidder / OEM {themselves or through reseller(s)}, should have executed project for supply and installation / commissioning of same or similar Category Products during preceding 3 financial years (i.e. current year and three previous financial years) as on opening of bid, as per following criteria:
- Single order of at least 35% of estimated bid value; or
  - Two orders of at least 20% each of estimated bid value; or
  - Three orders of at least 15% each of estimated bid value.
- Satisfactory Performance certificate issued by respective Buyer Organization for the above Orders should be uploaded with bid. In case of bunch bids, the Category related to primary product having highest bid value should meet this criterion
42. Warranty period of the supplied products shall be 3 years from the date of final acceptance of goods or after completion of installation, commissioning & testing of goods (if included in the scope of supply), at consignee location. OEM Warranty certificates must be submitted by Successful Bidder at the time of delivery of Goods. The seller should guarantee the rectification of goods in case of any break down during the guarantee period. Seller should have well established Installation, Commissioning, Training, Troubleshooting and Maintenance Service group in INDIA for attending the after sales service. Details of Service Centres near consignee destinations are to be uploaded along with the bid.

[This Bid is also governed by the General Terms and Conditions](#)

In terms of GeM GTC clause 26 regarding Restrictions on procurement from a bidder of a country which shares a land border with India, any bidder from a country which shares a land border with India will be eligible to bid in this tender only if the bidder is registered with the Competent Authority. While participating in bid, Bidder has to undertake compliance of this and any false declaration and non-compliance of this would be a ground for immediate termination of the contract and further legal action in accordance with the laws.

**---Thank You---**